




**Features:**

- suitable for roof pitches between 2-15 degrees
- Triple-glazed DU6 skylight
- perfect solution for passive houses
- sound reduction index Rw 34 dB
- can be used with roofing products as TPO, PVC, EPDM single ply or torched down membranes
- range of internal and external accessories available

**TECHNICAL SPECIFICATION**

**Flat roof skylight DXF DU6**



**I. APPLICATION**

Installation	required roof pitch 2° - 15°
	deck mounted

**II. FEATURES**

Frame structure	multi-chamber PVC profile insulated with polystyrene
Glazing	DU6 - triple pane passive glazing with TGI warm spacers, argon gas and two low-E coatings. Tempered external and laminated internal glass.
Termination Bar	included aluminum profiles to secure roofing membrane into the skylight frame
Opening method	non-opening
Warranty	5 years for skylights 20 years for laminated glass against hail (restrictions apply) 10 years for glass seal

**III. TECHNICAL PARAMETERS**

Technical parameters	Glazing unit type		
	Unit	DU6	Harmonised standards
U-factor for window	[BTU/h ft²F]	0.22	NFRC 100
U-factor for glazing unit	[BTU/h ft²F]	0.18	NFRC 100
Visible Transmittance factor	-	0.35	NFRC 200
Condensation Resistance	-	70	NFRC 500
SHGC	-	0.26	NFRC 200
Wind load resistance	Class C5/B5 Class C2/B2*		EN14351-1:2006+A2:2016
Impact resistance	Class 5 - 950 mm		EN14351-1:2006+A2:2016


\*for windows wider or longer than 55"

**IV. OPTIONAL ACCESSORIES**

Mounting accessories	- the XRD installation base allows raising the window above the roof by 6". Maximum 2 bases can be joined. - the XRD/W installation base allows raising the access roof light above the roof by 6". Maximum 3 bases can be joined. - the XRD/A installation base allows raising the roof light mounting angle by 3°.
External accessories	- AMZ/F Solar awning blind
Internal accessories	- ARF/D, ARF/D Z-wave blackout blinds - APF/D pleated blinds

V. DIMENSIONS

Size		30" x 30"	30" x 36"	36" x 36"	36" x 48"	48" x 48"
Rough opening (AxB)	in.	29 <sup>7</sup> / <sub>8</sub> x29 <sup>7</sup> / <sub>8</sub>	29 <sup>7</sup> / <sub>8</sub> x34 <sup>3</sup> / <sub>4</sub>	34 <sup>3</sup> / <sub>4</sub> x34 <sup>3</sup> / <sub>4</sub>	34 <sup>3</sup> / <sub>4</sub> x46 <sup>5</sup> / <sub>8</sub>	46 <sup>5</sup> / <sub>8</sub> x46 <sup>5</sup> / <sub>8</sub>
Outside frame (SxL)	in.	39 <sup>1</sup> / <sub>4</sub> x39 <sup>1</sup> / <sub>4</sub>	39 <sup>1</sup> / <sub>4</sub> x44 <sup>1</sup> / <sub>8</sub>	44 <sup>1</sup> / <sub>8</sub> x44 <sup>1</sup> / <sub>8</sub>	44 <sup>1</sup> / <sub>8</sub> x55 <sup>7</sup> / <sub>8</sub>	55 <sup>7</sup> / <sub>8</sub> x55 <sup>7</sup> / <sub>8</sub>



FAKRO America LLC  
39 W. Factory Road, Addison, IL  
Ph: 630-543-1010 / office@fakrousa.com