

DWF 60_L8B

SCH / DW / DWF



The FAKRO DWF60 fire-rated knee wall door provides safe access to non-livable spaces with E11/EI2 60 fire resistance. It features a removable handle that can stay in the door or be removed after use. The door is equipped with three seals: a perimeter gasket, a compression seal for airtight closure, and an intumescent seal that expands during fire to block air and smoke. The construction includes a pinewood frame, mineral wool insulation (3 1/8"), and a white HDF panel, ensuring durability and energy efficiency. Fully assembled, it supports universal left or right swing installation.

Functionality

Installation method	<ul style="list-style-type: none"> completely assembled; universal fit, left or right swing;
Fire-resistance [minutes]	E11/EI2 60
Fire resistance	Yes
Thermal insulation [R-value]	12
Equipment	<ul style="list-style-type: none"> trim; handle; expanding seal;
Insulation	Yes
Tightness class	4th highest class

Frame (dimensions)

Frame material	pinewood
Frame depth [inch]	3 9/16"
Frame element thickness [inch]	1 1/16"
Number of seals [pcs.]	2

Door sash

Door type	Fire-resistant
Door color	White
Thermal insulation thickness (US) [inch]	3 1/8"
Sash thickness (US) inch	3 3/8"

Frame size

SKU	Size	L - Outside frame dimension - height [inch]	W - Outside frame dimension - width [inch]	Inside frame dimension - height [inch]	Inside frame dimension - width [inch]
869485	21"x31"	31	21	29	19
869486	27"x35"	35	27	33	25
869487	27"x43"	43	27	41	25

