

# Oskorp Platina

## Product Description

Oskorp Platina is a premium, high-temperature, self-adhered roofing underlayment engineered for superior durability, adhesion, and weather resistance.

## Compliance

- ICC-ES AC188
- ASTM D1970
- TAS 103 (FBC HVHZ; Breathable!)



## Technical Data

Property	Standard / Method	Typical Value	Requirement
<b>Thickness</b>	-	<b>31 mil</b>	-
<b>Tensile Strength (MD/XMD)</b>	<b>D2523</b>	<b>51 / 40 lbf/in (post-UV)</b>	$\geq 25$ lbf/in
<b>Elongation at Break (Film) MD/XMD</b>	<b>D2523</b>	<b>408% / 434%</b>	$\geq 10\%$
<b>Peel Adhesion to Plywood (75°F)</b>	<b>D903</b>	<b>22.6 lbf/ft</b>	$\geq 12.0$ lbf/ft (D1970)
<b>Moisture Vapor Permeance</b>	<b>E96</b>	<b>9.5 perms</b>	-
<b>Flexibility @ -20°F</b>	<b>D1970</b>	<b>Pass</b>	No Cracking
<b>Compound stability 220°F</b>	<b>TAS103</b>	<b>Pass</b>	No flowing, dripping, nor drop formation
<b>Sealability Around Nail</b>	<b>D7349</b>	<b>Pass</b>	No Water Penetration
<b>Waterproof Integrity of Side Lap</b>	<b>TAS 103</b>	<b>Pass</b>	No Water Penetration
<b>Accelerated Aging (600 hrs)</b>	<b>AC188 / TAS 103</b>	<b>Pass</b>	No Damage / Delamination