



## CLAD WOOD ZOLA ARCTIC™

The highest performing window that money can buy, Zola Arctic combines a timber-aluminum frame with quad glazing, warm edge technology, and generous foam insulation to deliver unparalleled performance in a broad range of climates, including the extremely cold. A laminated, warp-resistant, solid timber construction frame. Triple compression air seals and exterior aluminum rainscreen cladding mounted on rails for an ultimate durability and rot resistance.

### PERFORMANCE

Frame Depth = 98mm (3.875")

CE Values:

$U_f = 0.689 \text{ W/(m}^2\text{K)}$

$U_g = 0.340 \text{ W/(m}^2\text{K)}$

$U_w = 0.511 \text{ W/(m}^2\text{K)}$

$\Psi_i = 0.016 \text{ W/(mK)}$

Fixed

Tilt-turn, Tilt-only, Turn-only, Tilt-first

Fixed/Operable combinations

### TIMBER & FINISH OPTIONS

Timbers available: finger jointed pine (base timber), Clear Pine, Meranti, European White Oak, and Larch.

Interior Finish Options: RAL painted timber, or standard set of interior stains.

Exterior Finish Options: RAL Standard, RAL FS Premium, Tactile Series, and Anodized options.

### CONFIGURATIONS AVAILABLE

### HARDWARE

European multi-point locking system with upto eight locking points on windows and four points on entry doors. Concealed hinges standard.

### SIZING

Min frame width = 450mm (17.7")



All performance data based on typical assemblies. Discuss specific performance values with a Zola Project Manager

Questions? Contact us for assistance at 303.578.0001