

TECHNICAL DATA SHEET

DELTA®-BUG SCREEN

MATERIAL

DELTA®-BUG SCREEN is made of extremely durable tear-resistant, flame-resistant, and clog-resistant polyester.

Suitable for use at all ventilation details with DELTA®-DRY, DELTA®-DRY STUCCO & STONE, and DELTA®-DRY & LATH. Strong and durable, keeps insects out of walls, while allowing full air movement for drying energy. Applies with standard roof nails or with cap nails.

- Insect and pest resistant
- Non-clogging
- Easy one man installation
- Stabilized against oxidation
- Easy to handle 5 foot strips
- Available in 20 pieces per bag
- Is easily cut with scissors or utility knife
- Suitable for DELTA®-DRY, DELTA®-DRY STUCCO & STONE, and DELTA®-DRY & LATH



Technical Data

Product name	DELTA®-BUG SCREEN	
Color	Silver-gray	
Material	Polyester	
Packaging	20 pieces per bag	
Length	5 ft (1.5 m)	
Width	1 1/2" (12 mm)	
Weight	1.8 lbs (.82 kg)	
Service life expectancy	> 20 years. Do not expose to UV light for more than 30 days.	



DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit www.dorken.com.